


ROTO 45.21 MCSS TECHNICAL DATA



- Maximum load capacity **4500 kg**
- Maximum lift height **20.8 metres**
- **Continuous turret rotation** achieved through a Merlo electro-hydraulic central rotary coupling
- Cab steel frame complying with the international **ISO 3449 Level II FOPS** (Falling Object Protective Structure) standard
- **Pneumatic suspension** seat
- **Electronic joystick** controls
- **Steering wheel tilt** adjustable by up to 16 degrees
- **Merlin system** (Merlo Local Interactive Network) providing a completely new way to automatically manage all the operating parameters and safety functions
- **MCSS system** (Merlin Continuous Slew Safety) adjusting automatically the load diagram to suit the stabiliser position chosen by the operator
- **Stabilizers** with independent extension and jacking
- **Hydropneumatic suspension** ensuring maximum driving comfort and stability when operating on tyres, by levelling the machine
- **Iveco** turbo intercooler **6 cylinder** engine, delivering **107 kW (145 HP)**
- **Hydrostatic transmission** utilising variable displacement motor and pump
- **Load-sensing** hydraulic pump
- Maximum speed **40 kph**

CHARACTERISTICS AND PERFORMANCE	45.21 MCSS
Total weight unladen, with forks (kg)	15050
Maximum load capacity (kg)	4500 ^(a)
Maximum lift height (m)	20.8 ^(a)
Maximum forward reach (m)	18
Lift height at maximum load capacity (m)	10.7
Forward reach at maximum load capacity (m)	7.6
Load capacity at maximum height (kg)	2500
Load capacity at maximum forward reach (kg)	750
Turret rotation (degrees)	Continuous
Engine (make/cylinder)	Iveco/6
Tier 3 engine power (kW/HP)	107/145
Fuel capacity (l)	150
Speed in the 1 st gear (kph)	16
Speed in the 2 nd gear (kph)	40
Load-Sensing hydraulic system (bar-l/min)	240-108
Hydraulic oil capacity (l)	160
Electrical circuit (V)	12
Battery (Ah)	160
Hydraulically controlled stabilizers	●
Hydropneumatic suspension	●
Cab compliant with FOPS standards	●
Tilting cab	-
Merlin electronic control system	●
Electro-mechanical joystick controls	-
Electronic joystick controls	●
Tac-Lock attachment coupling	● ^(a)
Auxiliary boom hydraulic service	●
Two floating forks (1,200 mm long)	●
Hydrostatic transmission	●
Hydrostatic oil capacity (l)	12
Finger-Touch direction reversing control	●
Permanent four-wheel drive	●
Four wheel steering	●
Service disk brakes on all wheels	●
Automatically locking parking brake	●
Tyres	18-22.5
Radio remote control	○
Pneumatic seat	●
Rear differential lock	○
Four cab working lights (2 f. + 2 r.)	○
Manual air conditioning system	○
Roof window wiper	○
Manual battery isolator	○
Front and roof sun shade	○

DIMENSIONS	45.21 MCSS
A (mm)	6600
C (mm)	2990
E (mm)	5030
F (mm)	330 ^(b)
H (mm)	2400
L (mm)	4950
M (mm)	995
N (mm)	2505
P (mm)	2990
R (mm)	4050
S (mm)	6580

